3M™ SAFETY AND SECURITY WINDOW FILMS




ULTRA PRESTIGE S70

Product Features & Benefits:

- Combination safety / solar control window film
- Micro-layered film designed for tear resistance
- Virtually clear film with heat rejection properties
- Helps protect from broken glass hazards
- Increase comfort and help reduce air conditioning costs
- Helps extend the life of furnishings by significantly reducing harmful UV rays

Applications:

- · Bomb Blast Mitigation
- · Building Envelope Protection
- Helping to Deter Break & Entry
- · Safety Glazing
- · Seismic Preparedness
- · Spontaneous Glass Breakage







Product Specifications

| Visible Light Transmittance | 42% |
|------------------------------------|-------|
| Glare Reduction | 22% |
| Solar Hear Gain Coefficient | .45 |
| Visible Light Reflectance Interior | 7% |
| Visible Light Reflectance Exterior | 6% |
| U-Value | 1.03 |
| UV Rejected | 99.9% |
| Shading Coefficient | .45 |
| Total Solar Energy Rejected | 48% |
| | |

^{*}Single Pane 1/4" (6mm) Clear

Film Properties

Ultra Prestige S70

| Film Thickness | 8 mils | |
|--------------------------------|---------------|--|
| Film Construction | Micro-layered | |
| TENSILE PROPERTIES (ASTM D882) | | |
| Tensile Strength | 25,600 psi | |
| Break Strength | 205 lbs/in | |
| Elongation at Break | 110% | |
| Yield Strength | 15,000 psi | |
| Elongation at Yield | 7% | |
| Modulus | 550 kpsi | |
| | | |

|] | Graves Area Tear Resistance (ASTM D | 1004) 1.150 lbs% | |
|---|-----------------------------------------------------|------------------|--|
| | Puncture-Propagation-Tear Resistance (AST | M D2582) 12 lbf | |
| | Puncture Strength (ASTM D4830) | 193 lbf | |
| 1 | Abrasion Resistance (ASTM D1044) | <5%∆Haze | |
| | Peel Strength (ASTM D3330) | 5.3 lb/in | |
| | Flammability (ASTM E84) | Class A | |
| | SOLAR PROPERTIES - Film applied to 1/4" clear glass | | |
| | Visible Light Transmitted | 42% | |
| | UV Light Rejected | 99.9% | |
| | | | |



3M Authorized Dealer & Applicator

Willoughby:

2174 Lost Nation Road Willoughby, Ohio 44094

Independence:

5005 Rockside Road, Suite 600 Cleveland, Ohio 44131

Toll Free: 800-295-8468

www.sunrayfilms.com

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specifications at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANANTY OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warrant the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



Commercial Solutions Division 3M Center, Building 220-12E-04 St. Paul, MN 55144 USA 3M.com/windowfilm

