



FeatherFriendly®

Authorized Exclusive Partner/Distributor of

BIRD DIVERT™



PRODUCT DETAILS

SPECIFICATIONS & CONSTRUCTION

Film Type: PVC acrylic hard coat
Adhesive Type: Pressure sensitive
Usage: Exterior
Thickness: 3.2 millimeters
Visible light reflectance: 2%
Visible light transmission: 98%
UV transmission: 98%
Solar heat reflectance: 2%
Solar heat transmission: 98%
Solar heat absorbance: 2%

Face film: 3.2 mil PVC with UV absorbing/reflective dot matrix
Adhesive: Adhesive clear, pressure sensitive
Release liner: Transparent, synthetic
Transfer tape: Transparent, synthetic

Threat level rating: 18
LEED credit: #55

INSTALL &
WARRANTY

5 YEARS

Installation should be in accordance with the Manufacturer's installation instructions. The film is applied using the same tools and techniques required for a dry install of window films.

Bird Divert™ product will be free from defects in material and manufacture for a period of **Five (5) years from the date of installation.**

DURABILITY &
LONGEVITY

10+ YEARS

TO PLACE AN ORDER, PLEASE SUBMIT:

- **Full client info for warranty registration**
- Rolls required or square footage of the project
- Date by which the product is required*
- Full billing and shipping address with delivery phone number

*Product and timeline will be confirmed at time of order placement

INSTALL VIDEO



INQUIRIES & ORDERS

John Susnik | Vice President

E sales@sunrayfilms.com
O 440.975.0800
TF 1.800.295.8468

A 2174 Lost Nation
 Rd. Willoughby,
 Ohio 44094

FeatherFriendly.com